


C4532X7R2A105K230KA (TDK item description : C4532X7R2A105KT****)

Applications		Commercial Grade
		Please refer to Part No. CGA8N2X7R2A105K230KA for automotive use.
Feature	Mid	Mid Voltage (100 to 630V)
Series	C4532 [EIA CC1812]	




Size	
Length(L)	4.50mm +/-0.40mm
Width(W)	3.20mm +/-0.40mm
Thickness(T)	2.30mm +/-0.20mm
Terminal Width(B)	0.20mm Min.
Terminal Spacing(G)	
Recommended Land Pattern(PA)	3.10 to 3.70mm
Recommended Land Pattern(PB)	1.20 to 1.40mm
Recommended Land Pattern(PC)	2.40 to 3.20mm
Recommended Slit Pattern(SD)	

Electrical Characteristics	
Capacitance	1uF +/-10%
Rated Voltage	100Vdc
Temperature Characteristic	X7R(+/-15%)
Dissipation Factor	3% Max.
Insulation Resistance	500MΩ Min.


Other	
Soldering Method	Reflow
AEC Q200	No
Packing	Blister (Plastic)Taping [180mm Reel]
Package Quantity	500Pcs Min.

C4532X7R2A105K230KA


Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




C4532X7R2A105K230KA




C4532X7R2A105K230KA




C4532X7R2A105K230KA



C4532X7R2A105K230KA



C4532X7R2A105K230KA(DC Bias = 0V) C4532X7R2A105K230KA(DC Bias = 50V)



C4532X7R2A105K230KA(100kHz) C4532X7R2A105K230KA(500kHz)
C4532X7R2A105K230KA(1MHz)