

Part- number: G51MA7- P04LJG0-0060



ODU MEDI- SNAP® Receptacle

4- positions

Receptacle - Protection class IP 50, for strain relief, for front and rear mounting

Anti- rotation feature


Housing: PSU grey

(example)

Dimensions



Positions: 4positions



Contact insert

4positions

Socket

Solder termination

Coding 40°



Material Insulator:	PEEK
Contact diameter:	0.9
Cable diameter:	from 0 mm to 0 mm
Wire cross section:	AWG 22 / 0.38 mm ²
Solder bucket diameter:	0.85 mm

Technical information

Resistance:	< 4.5 μΩ	
Insulation resistance:	10 ^ 16 Ω	
max. creepage and clearance distance:	1.2 mm	according to IEC 60664-1:2007 (VDE 0110-1:2008)
Current load single contact:	10 A	
Current load entire insert:	10 A	VDE 0298-4:2013
Test voltage:	1.9 kV	SAE AS 13441:2004 method 3001.1
Reference voltage:	0.6 kV	SAE AS 13441:2004 method 3001.1

All dimensions in mm. All images are just illustrations. Changes reserved.

General Information ODU MEDI- SNAP

Operating Temperature: -50°C up to +120°C

Short term (e.g. for autoclaving) up to +140°C

Mating Cycles:> 2,000

- Housing 100% touch proof
- Light- weight
- Low mating and demating forces

ODU GmbH & Co. KG

Pregelstraße 11
84453 Mühldorf / Inn

Phone: +49 8631 6156-0

Fax: +49 8631 6156-49

E- Mail: zentral@odu.de