



Intel® 82801CA I/O Controller

SPECIFICATIONS

ORDERING / SSPECS / STEPPINGS

Specifications

Status	Launched
Launch Date	Q4'03
Embedded Options Available	Yes
Supplemental SKU	No
Max TDP	2 W
Recommended Customer Price	6 (32/33)
PCI Support	USB 1.0
USB Revision	6
# of USB Ports	0
# of SATA Ports	10/100
Integrated LAN	1 Channel
Integrated IDE	31mm x 31mm
Package Size	See MDDS
Low Halogen Options Available	No
Intel® Trusted Execution Technology	No
Intel® Active Management Technology	No
Intel® Quick Resume Technology	No
Intel® Quiet System Technology	No
Intel® HD Audio Technology	No
Intel® AC97 Technology	No
Intel® Matrix Storage Technology	

ORDERING AND SPEC INFORMATION

Retired and Discontinued 82801CA Integrated Controller Hub (ICH3 -S)

PBGA421	B2	2 W	NH82801CA	SL8AN		4A994	NA	8542310000-CHPST	

“Announced” SKUs are not yet available. Please refer to the Launch Date for market availability.

The Recommended Customer Price^(RCP) is pricing guidance for Intel products. Prices are for direct Intel customers and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply.Listing of these RCPdoes not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numberAny use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter ofrecord, and as such, your company is responsible for determining the correct classification of any item at the time of export.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See http://www.intel.com/products/processor_number for details.

Hyper-Threading Technology (HT Technology) requires a computer system with an Intel® processor supporting HT Technology and an HT Technology enabled chipset, BIOS and operating system. Performance will vary depending on the specific hardware and software you use. See www.intel.com/products/ht/hyperthreading_more.htm for more information including details on which processors support HT Technology.

64-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. Consult with your system vendor for more information.

Max Turbo Frequency refers to the maximum singlecore frequency that can be achieved with Intel® Turbo Boost Technology, which requires a PC with a processor with Intel Turbo Boost Technology capability. Intel Turbo Boost Technology performance varies depending on hardware, software, and overall system configuration. Check with your PC manufacturer on whether your system delivers Intel Turbo Boost Technology. Seewww.intel.com/technology/turboboost/ for more information.

Enabling Execute Disable Bit functionality requires a PC with a processor with Execute Disable Bit capability and a supported operating system. Check with your PC manufacturer on whether your system delivers Execute Disable Bit functionality.

Intel® Virtualization Technology requires a computer system with a processor, chipset, BIOS, virtual machine monitor (VMM) and for some uses, certain platform software, enabled for it. Functionality, performance or other benefit will vary depending on hardware and software configurations. Intel Virtualization Technology -enabled VMM applications are currently in development.

System and Maximum TDP is based on worst case scenarios.Actual TDP may be lower if not all I/Os for chipsets are used.

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cyclespecifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed.Please contact system vendor for more information on specific products or systems.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final productIntel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

COMPARE PRODUCTS

- [Add to Compare](#)
- [Compare Now](#)

- [Visit the Embedded Design Center >](#)

QUICK LINKS

- [Products formerly ICH3](#)
- [Download Datasheet](#)
- [Search Distributors](#)

ADDITIONAL INFORMATION

PCN/MDDS INFORMATION

SL8AN
868447 : [PCN](#) | [MDDS](#)

SL632
843132 : [PCN](#) | [MDDS](#)