
Hart-Lock™ Complex Environment Locking Devices

2-Pole, 3-Wire Grounding
15A, 125V/AC
NEMA L5-15



L5-15R L5-15P

Hart-Lock Plugs & Connectors

Rating A	Rating V/AC	NEMA	Description	Cord Diameter	Color	Plug Catalog No.	Connector Catalog No.	
15	125	L5-15	Watertight	0.30-0.65" (7.6-16.5mm)	Y	☐ 24W47*	☐ 25W47*	•
			Watertight	0.30-0.65" (7.6-16.5mm)	BK	☐ 24W47BK*	☐ 25W47BK*	•
			AutoGrip Corrosion Resistant	0.33-0.66" (8.4-16.7mm)	Y	☐ 4721NCR	☐ 4731NCR	•

* Not Fed. Spec.




2447


Hart-Lock Receptacles

Rating A	Rating V/AC	NEMA	Description	Color	Single Receptacle Catalog No.	Duplex Receptacle Catalog No.	
15	125	L5-15	Watertight	Y	☐ 65W47Δ†	☐ 65W47DPLXΔ†	•
			Watertight	BK	☐ 65W47BKΔ†	☐ 65W47DPLXBKΔ†	•
			Corrosion Resistant	Y	--	☐ CR4700	•
		5-15/ L5-15	Corrosion Resistant Combination Locking & Straight Blade	Y	--	☐ CR5792	•

Δ cULus Listed, † Not CSA Certified




25W47



CR5792

Hart-Lock™ Complex Environment Locking Devices

2-Pole, 3-Wire Grounding
15A, 250V/AC
NEMA L6-15



L6-15R L6-15P

Hart-Lock Plugs & Connectors

Rating A	Rating V/AC	NEMA	Description	Cord Diameter	Color	Plug Catalog No.	Connector Catalog No.	
15	250	L6-15	Watertight	0.30-0.65" (7.6-16.5mm)	Y	☐ 24W49	☐ 25W49	•
			Watertight	0.30-0.65" (7.6-16.5mm)	BK	☐ 24W49BK	☐ 25W49BK	•
			Severe Duty	0.33-0.66" (8.4-16.7mm)	Y & BK	☐ 2449	☐ 2549	

Hart-Lock Receptacles

Rating A	Rating V/AC	NEMA	Description	Single Receptacle Catalog No.	Duplex Receptacle Catalog No.	
15	250	L6-15	Watertight	☐ 65W49	☐ 65W49DPLX	
			Watertight	☐ 65W49BK	☐ 65W49DPLXBK	

Color Information:
Colors: BK (Black), Y (Yellow)

BK (Black) Y (Yellow)

Specifications and availability are subject to change without notice.

Indicates NAFTA Compliant - Page R-30

Dimensional Information: D-9

Specification Information:
Watertight Industrial Plugs & Connectors: D-34
Severe Duty Industrial Plugs & Connectors: D-35
Corrosion Resistant AutoGrip Industrial Plugs & Connectors: D-35