




SECT.A-A



SECT.B-B

注記

1. 適合ハウジング: 51067-**00

リン青銅, 錫メッキ (t=0.254)	50217-8100	バラ状
	50217-8000	連鎖状
黄銅, 錫メッキ (t=0.254)	50217-9101	バラ状
	50217-9001	連鎖状
材 料	ENG. NO.	端子形状

角度	ANGLE	±3°
30°以上 OVER	±0.3	A 変更 (J00226)
10°以上 30°未満 OVER UNDER	±0.25	0 新規作成 (J91079)
10°未満 UNDER	±0.2	記号 LTR 変更内容 DR. CHK. 日付
一般公差 GENERAL TOLERANCES		

材料 MATERIAL	仕上げ FINISH	適用電線範囲 WIRE RANGE	被覆外径 INS. RANGE	DRAWN BY '89-12-19 K.ASAKAWA	CHK'D BY '90/11/15 M.FUKUSHIMA
AWG#18~#24	φ1.4 ~ φ3.0	APP'D BY '90/11/15 M.ENOMOTO	尺 度 SCALE	REVISE ONLY ON CAD SYSTEM	

材料 MATERIAL		MOLEX-JAPAN CO.,LTD. 日本モレックス株式会社	
仕上げ FINISH		EDP. NO.	
適用電線範囲 WIRE RANGE		ENG. NO.	REV
被覆外径 INS. RANGE		SD-50217-*****	A
DRAWN BY '89-12-19 K.ASAKAWA		TITLE 名称 3.5 WIRE TO BOARD CONN. CRIMP RECEPTACLE	
APP'D BY '90/11/15 M.ENOMOTO		尺 度 SCALE	

