Friday, 18 November, 2005

CATALOG

- **Cross Reference**
  - Competitive Products
  - Military Spec P/Ns
  - Tyco Brand P/Ns
- Part Number Search
- Document Search
- Product Type Search
- Product Family Search
- Alphabetical Search
- RoHS/ELV Compliance & Alternates
- CAD Model Search
- Brand Search
- Tool Search
- Multiple Part Comparison
- Lead Free Solutions
- Help/Glossary

Home

e-bulletin newsletter
SUBSCRIBE NOW!
click here

Multimate Contacts
↳ Multimate

AMP **200336-1** Active

Directive 2002/95/EC Compliant RoHS Compliant

(Corporate P/N: 200336-1)

Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
General Info Sales Info Assembly Subcontractors	Pricing & Availability	Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

Product Photo

Searchable Features:	
Brand:	AMP
RoHS/ELV Compliance:	RoHS compliant, ELV compliant
Lead Free Solder Processes:	Not relevant for lead free process
Pin/Socket:	Pin
High Current:	No
Contact Mating Area Plating:	Gold (30) over Nickel (50)
Wire Range (mm [AWG]):	0.80 - 1.40² [18-16]
Contact Material:	Brass
Product Type:	Type II
Contact Size:	16

Other Properties:	
Pin Diameter (mm [in]):	1.57 [0.062]
Wire/Cable Type:	Discrete Wire
Test Current (Amps.):	13.0
Color Code:	Blue/Blue
Grade:	Commercial
Used With:	G Series Connectors, M Series Connectors, CPC Connectors
Contact Retention Method:	Retention Spring
Retention Spring Material:	Stainless Steel

Contact Type:	Signal
Terminate To:	Wire
Insulation Support:	No
Wire Termination Type:	Crimp
Packaging Method:	Loose Piece

Comment:	Use turret TH502 (p/n 1-601967-6) with hand tool 601967-1. Extraction Tool No. 305183 Insertion Tool No. 200893-2 (for insulation diameters 1.78 [.070] or less).

Copyright and Privacy Statement
Visit Tyco International Ltd.