





LOC	DIST	REVISIONS					
GP	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			F1	REVISED PER ECO-11-004835	11MAR11	RK	HMR




RECOMMENDED PC BOARD LAYOUT (VIEWED FROM CONNECTOR SIDE)



SECTION U-U

OBSOLETE	BLUE	78.74 [3.100]	31	80.77 [3.180]	86.26 [3.396]	88.90 [3.500]	64	3-1761608-7		
		73.66 [2.900]	29	75.69 [2.980]	81.18 [3.196]	83.82 [3.300]	60	3-1761608-6		
		60.96 [2.400]	24	62.99 [2.480]	68.48 [2.696]	71.12 [2.800]	50	3-1761608-5		
		53.34 [2.100]	21	55.37 [2.180]	60.86 [2.396]	63.50 [2.500]	44	3-1761608-4		
		48.26 [1.900]	19	50.29 [1.980]	55.78 [2.196]	58.42 [2.300]	40	3-1761608-3		
		43.18 [1.700]	17	45.21 [1.780]	50.70 [1.996]	53.34 [2.100]	36	3-1761608-2		
		40.64 [1.600]	16	42.67 [1.680]	48.16 [1.896]	50.80 [2.000]	34	3-1761608-1		
		35.56 [1.400]	14	37.59 [1.480]	43.08 [1.696]	45.72 [1.800]	30	3-1761608-0		
		30.48 [1.200]	12	32.51 [1.280]	38.00 [1.496]	40.64 [1.600]	26	2-1761608-9		
		27.94 [1.100]	11	29.97 [1.180]	35.46 [1.396]	38.10 [1.500]	24	2-1761608-8		
22.86 [.900]		9	24.89 [.980]	30.38 [1.196]	33.02 [1.300]	20	2-1761608-7			
17.78 [.700]		7	19.81 [.780]	25.30 [.996]	27.94 [1.100]	16	2-1761608-6			
15.24 [.600]		6	17.27 [.680]	22.76 [.896]	25.40 [1.000]	14	2-1761608-5			
10.16 [.400]		4	12.19 [.480]	17.68 [.696]	20.32 [.800]	10	2-1761608-3			
OBSOLETE		7.62 [.300]	3	9.65 [.380]	15.14 [.596]	17.78 [.700]	8	2-1761608-2		
		5.08 [.200]	2	7.11 [.280]	12.60 [.496]	15.24 [.600]	6	2-1761608-1		
		OBSOLETE	BLACK	73.66 [2.900]	29	75.69 [2.980]	81.18 [3.196]	83.82 [3.300]	60	1-1761608-6
				60.96 [2.400]	24	62.99 [2.480]	68.48 [2.696]	71.12 [2.800]	50	1-1761608-5
				48.26 [1.900]	19	50.29 [1.980]	55.78 [2.196]	58.42 [2.300]	40	1-1761608-3
				40.64 [1.600]	16	42.67 [1.680]	48.16 [1.896]	50.80 [2.000]	34	1-1761608-1
	35.56 [1.400]			14	37.59 [1.480]	43.08 [1.696]	45.72 [1.800]	30	1-1761608-0	
	30.48 [1.200]			12	32.51 [1.280]	38.00 [1.496]	40.64 [1.600]	26	1761608-9	
	27.94 [1.100]			11	29.97 [1.180]	35.46 [1.396]	38.10 [1.500]	24	1761608-8	
	22.86 [.900]			9	24.89 [.980]	30.38 [1.196]	33.02 [1.300]	20	1761608-7	
17.78 [.700]	7			19.81 [.780]	25.30 [.996]	27.94 [1.100]	16	1761608-6		
15.24 [.600]	6			17.27 [.680]	22.76 [.896]	25.40 [1.000]	14	1761608-5		
10.16 [.400]	4	12.19 [.480]	17.68 [.696]	20.32 [.800]	10	1761608-3				
HOUSING COLOR	E	D	C	B	A	NO OF POS	PART NUMBER			

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN: 30JUN05 B.CRISAMORE/DTI CHK: 30JUN05 S.BOLASH		 TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 P/LC ± — 1 P/LC ± — 2 P/LC ± — 3 P/LC ± 0.13[.005] 4 P/LC ± — ANGLES ± —		NAME AFVD 30JUN05 M.WALMSLEY	
		PRODUCT SPEC — APPLICATION SPEC —		HEADER ASSEMBLY, SHORT EJECT LATCH, VERTICAL, LOW PROFILE, IDC —	
MATERIAL 		FINISH 		SIZE A1	CAGE CODE 00779
		WEIGHT —		DRAWING NO 1761608	RESTRICTED TO —
CUSTOMER DRAWING				SCALE 4:1	SHEET 1 OF 1
				REV F1	