

Part Number: C6353A

Revision: 4/11/2014

4C 20AWG PVC, UNSH, PVC**COMMUNICATION AND CONTROL CABLE****A. CONSTRUCTION****DIAMETERS**

Conductor:	#20 AWG (7/28) Tinned Copper	.036" Nom
Insulation:	.016" Wall, Polyvinyl Chloride (PVC)	.068" Nom
Cable Assembly:	4 Conductors with a 4.00" LHL	.164" Nom
Ripcord:	None	
Jacket:	.032" Wall, Polyvinyl Chloride (PVC)	.230" ± .011"
Sequential Footage:	Yes	
Print Legend:	<i>CAROL (R) 20 AWG -- C6353A -- 75C E105765-H CM (UL) C(UL) OR AWM STYLE 2464/2576 -- CSA LL69381 60C CMG -- MADE IN USA (date code - MM/YY) (sequential footage)</i>	

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM
UL Standard 758	AWM Style 2464/2576
CSA International	Type CMG
EU Directive 2011/65/EU (RoHS-2)	RoHS Compliant

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +80°C
Suggested Working Voltage:	300 Vrms (Max)
Conductor DCR:	10.9 Ohms/1000ft (Max) @ 20°C
Capacitance (Cond-Cond):	27.5 pF/ft (Nom) @ 1kHz

D. COLOR CODE

COND	COLOR
1	BLACK
2	WHITE
3	RED
4	GREEN

E. CUSTOMER APPROVAL

Signature: _____

Date: _____