



Representative

Catalog Number: DS3516MP000
Product ID: 7TAA057030R0667
UPC Number: 70891718545
Status: A

MaxGuard Male Plug, 30 Amp, 4 Pole 5 Wire, 30 Y 120/208V, 60Hz

North American Specifications (UNSPSC)

UNSPSC	39121402 Electrical plugs
IGCC	4526 Electrical plugs
Type	MaxGuard Interconnection Systems
Special Features	Waterproof construction provides environmental separation at the front of each device (they don't have to be connected together just to be called "watertight").
Application	For use in "People Movers" which require air conditioning and heater unit power when docked at end of line locations for maintenance and overhaul, ex: Dulles Airport.
Standard	UL E68085
Number Of Poles	4
Number Of Wires	5
Amperage Rating	30 Amps
Voltage Rating	120/208 V
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	30A
Construction type	Plug
Number of poles	4

Packaging

Outer Quantity	1
Outer Dimensions (inches)	8.63x4.75x4.63
Weight Uom	3 lbs. Each

Documents / Support Tools

Catalog Page	Available on Website
--------------	----------------------

For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com