



OD753J

OHMITE

Buy Now



Looking for a discount?

[Check out our current promotions!](#)

Give us a call

1-855-837-4225

International: 1-415-281-3866

Email Us

Sales and New Orders: sales@verical.com

Order Support: support@verical.com

Suppliers: [Visit our seller page](#)


Company Address

Arrow Electronics, Inc
9201 East Dry Creek Road
Centennial, CO 80112

This coversheet was created by Verical, a division of Arrow Electronics, Inc. ("Verical"). The attached document was created by the part supplier, not Verical, and is provided strictly 'as is.' Verical, its subsidiaries, affiliates, employees, and agents make no representations or warranties regarding the attached document and disclaim any liability for the consequences of relying on the information therein. All referenced brands, product names, service names, and trademarks are the property of their respective owners.

Little Demon®

Carbon Composition Molded Resistors OD/OF Series - 5% Tolerance OA Series -10% Tolerance



Series	Wattage	Ohms	Dimensions (in. / mm)		Max. Voltage	Dielectric VAC	Lead Dia.
			Length	Max Diam.			
OD	0.25	2.2-5.6M	0.276 / 7.0	0.098 / 2.5	250	500	.027 / .69
OF	0.50	2.2-20M	0.406 / 10.3	0.150 / 3.8	350	700	.029 / .75
OA	1.00	2.2-1M	0.591 / 15.0	0.236 / 6.0	500	1000	.035 / .92

Ohmite's Little Demons are small, reliable carbon composition resistors with exceptional strength. They are made tough by a molding process that combines the leads, insulation and resistive element into an integrated unit. Along with their small size, Little Demons perform with low noise, dissipate heat rapidly and offer high temperature stability.

Color codes are readable even after prolonged use thanks to a very durable coating that resists abrasions and chipping normally associated with automatic insertion equipment.

FEATURES

- Molded insulation for high dielectric strength.
- Rugged construction.
- Available in Resistor Cabinet Assortments & 100 pc packs.
- High surge capabilities.
- Comparable to "Mil" RC07, RC20, and RC32 types.

SPECIFICATIONS

Material

Terminals: Solder-coated copper lead.

Body: Molded Phenolic

Electrical

Tolerance: ±5% (OD/OF); ±10% (OA)

Derating: Linearly from 100% @ +70°C to 0% @ 130°C

ORDERING INFORMATION

OD 68 3 J

Series	Ohms	Tolerance
OD	68G = 6.8	J = 5%
OF	680 = 68	K = 10%
OA	681 = 680	
	682 = 6,800	
	683 = 68,000	
	684 = 680,000	

STOCK PART NUMBERS FOR STANDARD RESISTANCE VALUES

Ohmic value	Part No. Prefix	Wattage			Ohmic value	Part No. Prefix	Wattage			Ohmic value	Part No. Prefix	Wattage			Ohmic value	Part No. Prefix	Wattage		
		OD	OF	OA			OD	OF	OA			OD	OF	OA			OD	OF	OA
2.2		✓	✓	✓	56		✓	✓	✓	1,600		✓	✓	✓	47,000		✓	✓	✓
2.4		✓	✓	✓	62		✓	✓	✓	1,800		✓	✓	✓	51,000		✓	✓	✓
2.7		✓	✓	✓	68		✓	✓	✓	2,000		✓	✓	✓	56,000		✓	✓	✓
3		✓	✓	✓	75		✓	✓	✓	2,200		✓	✓	✓	62,000		✓	✓	✓
3.3		✓	✓	✓	82		✓	✓	✓	2,400		✓	✓	✓	68,000		✓	✓	✓
3.6		✓	✓	✓	91		✓	✓	✓	2,700		✓	✓	✓	75,000		✓	✓	✓
3.9		✓	✓	✓	100		✓	✓	✓	3,000		✓	✓	✓	82,000		✓	✓	✓
4.3		✓	✓	✓	110		✓	✓	✓	3,300		✓	✓	✓	91,000		✓	✓	✓
4.7		✓	✓	✓	120		✓	✓	✓	3,600		✓	✓	✓	100,000		✓	✓	✓
5.1		✓	✓	✓	130		✓	✓	✓	3,900		✓	✓	✓	110,000		✓	✓	✓
5.6		✓	✓	✓	150		✓	✓	✓	4,300		✓	✓	✓	120,000		✓	✓	✓
6.2		✓	✓	✓	160		✓	✓	✓	4,700		✓	✓	✓	130,000		✓	✓	✓
6.8		✓	✓	✓	180		✓	✓	✓	5,100		✓	✓	✓	150,000		✓	✓	✓
7.5		✓	✓	✓	200		✓	✓	✓	5,600		✓	✓	✓	160,000		✓	✓	✓
8.2		✓	✓	✓	220		✓	✓	✓	6,200		✓	✓	✓	180,000		✓	✓	✓
9.1		✓	✓	✓	240		✓	✓	✓	6,800		✓	✓	✓	200,000		✓	✓	✓
10		✓	✓	✓	270		✓	✓	✓	7,500		✓	✓	✓	220,000		✓	✓	✓
11		✓	✓	✓	300		✓	✓	✓	8,200		✓	✓	✓	240,000		✓	✓	✓
12		✓	✓	✓	330		✓	✓	✓	9,100		✓	✓	✓	270,000		✓	✓	✓
13		✓	✓	✓	360		✓	✓	✓	10,000		✓	✓	✓	300,000		✓	✓	✓
15		✓	✓	✓	390		✓	✓	✓	11,000		✓	✓	✓	330,000		✓	✓	✓
16		✓	✓	✓	430		✓	✓	✓	12,000		✓	✓	✓	360,000		✓	✓	✓
18		✓	✓	✓	470		✓	✓	✓	13,000		✓	✓	✓	390,000		✓	✓	✓
20		✓	✓	✓	510		✓	✓	✓	15,000		✓	✓	✓	430,000		✓	✓	✓
22		✓	✓	✓	560		✓	✓	✓	16,000		✓	✓	✓	470,000		✓	✓	✓
24		✓	✓	✓	620		✓	✓	✓	18,000		✓	✓	✓	510,000		✓	✓	✓
27		✓	✓	✓	680		✓	✓	✓	20,000		✓	✓	✓	560,000		✓	✓	✓
30		✓	✓	✓	750		✓	✓	✓	22,000		✓	✓	✓	620,000		✓	✓	✓
33		✓	✓	✓	820		✓	✓	✓	24,000		✓	✓	✓	680,000		✓	✓	✓
36		✓	✓	✓	910		✓	✓	✓	27,000		✓	✓	✓	750,000		✓	✓	✓
39		✓	✓	✓	1,000		✓	✓	✓	30,000		✓	✓	✓	820,000		✓	✓	✓
43		✓	✓	✓	1,100		✓	✓	✓	33,000		✓	✓	✓	910,000		✓	✓	✓
47		✓	✓	✓	1,200		✓	✓	✓	36,000		✓	✓	✓	1 MEG		✓	✓	✓
51		✓	✓	✓	1,300		✓	✓	✓	39,000		✓	✓	✓	1.1 MEG		✓	✓	✓
					1,500		✓	✓	✓	43,000		✓	✓	✓	1.2 MEG		✓	✓	✓