

OCEANOGRAPHIC ISO-CURVE® INTERCHANGEABLE THERMISTORS

Ro @ 25°C Ohms	Temp. Tol. Over Temp Range (± °C)	Code Number	Fig.	Temp. Range °C	Ratio	R-T Curve Ref. Page 30	D.C.	T.C.	Lead Dia.	Lead Mat'l	L	D	B	T	Tinned
-------------------	--	----------------	------	-------------------	-------	------------------------------------	------	------	--------------	---------------	---	---	---	---	--------

OCEANOGRAPHIC ISO-CURVE® INTERCHANGEABLE R-T CURVED MATCHED THERMISTORS

Sub-Mini-Probe

SEE ISO-CURVE CATALOG L-2B

15,000	.1	GB42SMM1	22	-5 to +35	—	15K	.6	2.6	.003	PT-IR	¼	.060	.280	—	—
--------	----	----------	----	-----------	---	-----	----	-----	------	-------	---	------	------	---	---

Mini-Probe

2,001	.1	GB32MM172	22	-5 to +35	—	2K	1.4	16	.008	Tinned Dumet	1⅜	.120	½	—	—
4,002	.1	GB34MM132	22	-5 to +35	—	4K	1.4	16	.008	Tinned Dumet	1⅜	.120	½	—	—

Standard Probe

2,001	.1	GB32PM82	22	-5 to +35	—	2K	1.9	25	.012	Tinned Dumet	2	.180	½	—	—
4,002	.1	GB34PM62	22	-5 to +35	—	4K	1.9	25	.012	Tinned Dumet	2	.180	½	—	—

Small Bead

4,002	.1	GB34JM14	23A	-5 to +35	—	4K	.2	1	.001	PT-IR	¼	.040	.030	—	—
-------	----	----------	-----	-----------	---	----	----	---	------	-------	---	------	------	---	---

Standard Bead

2,001	.1	GB32JM19	23	-5 to +35	—	2K	.8	2	.004	PT-IR	⅝	.100	.060	—	—
4,002	.1	GB34JM13	23	-5 to +35	—	4K	.8	2	.004	PT-IR	⅝	.100	.060	—	—

UNI-CURVE® INTERCHANGEABLE THERMISTORS


Ro @ 25°C Ohms	Temp. Tol. Over Temp Range (± °C)	Code Number	Fig.	Temp. Range °C	Ratio	R-T Curve Ref. Pages 30 and 31	D.C.	T.C.	Lead Dia.	Lead Mat'l	L	D	B	T	Tinned
-------------------	--	----------------	------	-------------------	-------	--	------	------	--------------	---------------	---	---	---	---	--------

UNI-CURVE® R-T CURVE MATCHED THERMISTORS

SEE UNI-CURVE CATLOG L-6B

100	±0.2	UUD21J1	24	-20°C to 50°C	—	100	1	10	.008	Tinned Copper Alloy	1½	.095	—	—	—
300	±0.2	UUD23J1	24	-20°C to 50°C	—	300	1	10	.008	1½	.095	—	—	—	—
500	±0.2	UUB25J1	24	0°C to 70°C	—	500	1	10	.008	1½	.095	—	—	—	—
1,000	±0.2	UUB31J1	24	0°C to 70°C	—	1,000	1	10	.008	1½	.095	—	—	—	—
2,252	±0.2	UUA32J3	24	0°C to 70°C	—	2,252	1	10	.008	1½	.095	—	—	—	—
3,000	±0.2	UUA33J1	24	0°C to 70°C	—	3,000	1	10	.008	1½	.095	—	—	—	—
5,000	±0.2	UUA35J1	24	0°C to 70°C	—	5,000	1	10	.008	1½	.095	—	—	—	—
10,000	±0.2	UUA41J1	24	0°C to 70°C	—	10,000	1	10	.008	1½	.095	—	—	—	—
10,000	±0.2	UUF41J2	24	0°C to 70°C	—	10,000	1	10	.008	1½	.095	—	—	—	—
30,000	±0.2	UUR43J1	24	0°C to 70°C	—	30,000	1	10	.008	1½	.095	—	—	—	—
30,000	±0.2	UUT43J1	24	0°C to 70°C	—	30,000	1	10	.008	1½	.095	—	—	—	—
50,000	±0.2	UUT45J1	24	0°C to 70°C	—	50,000	1	10	.008	1½	.095	—	—	—	—
100,000	±0.2	UUT51J1	24	0°C to 70°C	—	100,000	1	10	.008	1½	.095	—	—	—	—
2,252	±0.2	UUA32J4	24	0°C to 100°C	—	2,205	1	10	.008	1½	.095	—	—	—	—
3,000	±0.2	UUA33J4	24	0°C to 100°C	—	3,000	1	10	.008	1½	.095	—	—	—	—
5,000	±0.2	UUA35J3	24	0°C to 100°C	—	5,000	1	10	.008	1½	.095	—	—	—	—
10,000	±0.2	UUA41J8	24	0°C to 100°C	—	10,000	1	10	.008	1½	.095	—	—	—	—


EXPERIMENTERS MOUNTING HARDWARE KITS — H100



ASSEMBLY H101



ASSEMBLY H102



ASSEMBLY H103

KIT H-100
CONTAINS H101, H102, & H103

*Available also as UUR43J1; reference curve No. 18, page 29.




FIG. 22
ISO-CURVE
GLASS PROBES
SERIES




FIG. 22A
ISO-CURVE
GLASS PROBES
PARALLEL




FIG. 23
ISO-CURVE
GLASS BEADS
SERIES




FIG. 23A
ISO-CURVE
GLASS BEADS
PARALLEL




FIG. 24
UNI-CURVE DISCS




FIG. 25
WASHER ASSEMBLY